

ADENPAL LLC
info@apledworld.com
www.apledworld.com
+1 713-471-6021

P/N: AST-HB18-240WS1XYA1-abcde

Note:

AST= Company name;

HB18 = Product series, LED High Bay Light;

240W= Rating Power;

S1= Driver manufacturer, LiFUD or SOSEN series;

"X" can be any alphabet for manufacturer of LED;

"Y" can be "T1-T9" "CP" for Diffuser type;

A1= Version number;

"a" can be any two letters to represent lamp colors; BH=Black, WH=White, or Customized;

"b" can be "S" or blank for Surge-protective Device provided or not;

"c" can be "M" or blank for Motion microwave Sensor, provided or Motion PIR sensor or not



"d" can be any digits for CCT, 30-65K(3000-6500K)

"e" can be "RP", "RA" or blank for Thermoplastic shade, aluminum shade provided or not.





DIMENSIONS

Pendent



Surface-mounted



ADVANTAGE

- UL cUL certificate.
- Lumileds or Samsung Chip, high CRI.
- Input voltage 120-277VAC.
- Output constant current lever can be adjusted through output cable with 0-10V.
- No UV or IR in the beam.
- Easy to install and operate.
- Energy saving, long lifespan.
- Light is soft and uniform, safe to eyes.
- Instant start, NO flickering, NO humming.
- Green and eco-friendly without mercury.

APPLICATION

- Warehouse, factory and workshops;
- Highway toll station and gas station;
- Exhibition hall;
- Gymnasium and supermarkets, etc.


SPECIFICATIONS

OPTICAL	Input Power (Tolerance : ±10%)	240W
	Color Temperature	3000K-6500K
	Lumen (Tolerance : -10%)	31700LM-34800LM
	Efficacy (Tolerance : -3%)	132LM/W-145LM/W
	CRI	>80
	Color Consistency	<6 Steps (or <6 SDCM)
	UGR	<28 (X=4H, Y=8H; S/H=1; Reflectances: 70%/50%/20%)
	Diffuser Type	PC Lens
	Beam Angle (50%) (Tolerance : ±15%)	90 Degree
ELECTRICAL	Input Voltage and Frequency	120-277VAC, 50/60Hz
	PF (Tolerance : -3%)	≥0.9
	THD (Tolerance : +5%)	≤20%
	Flicker Percent	<10%
	Driver Brand	China Brand Driver (0-10V dimming)
	Driver Model	LF-FHB200YAIIV or SS-240CNL-260BH
	Driver Surge protection	L/N-PE: 6kV, L-N: 6kV
	Dimming	0-10V dimming standard
	Optional Accessory	Motion Sensor, PIR sensor, Surge-protective Device
MATERIALS	LED Brand	Lumileds
	LED Type	SMD2835
	LED QTY	400PCS
	Housing	Die-cast aluminum
	Housing Color	Black, White, or Customized
	Waterproof Rating	WET (IP65)
OTHERS	Operating Temperature	Without Motion Sensor: -40℃ TO 50℃
		With Motion Sensor: -30℃ TO 50℃
	Storage Temperature	-40℃ TO 80℃
	Operating Humidity	20% - 90% RH
	Storage Humidity	10% - 95% RH
Warranty	5 years	

PACKAGE

Lamp Type	Carton Size	Qty / Carton	Net Weight / Carton	Gross Weight / Carton
Pendent	340*340*145mm	1 PC	2.6KG	3.3KG
Surface-mounted	340*340*145mm	1 PC	3.3KG	4.2KG

Tolerance of Carton Size: ±15 MM, Tolerance of Weight: ±10%.



LIGHT DISTRIBUTION TESTING PARAMETERS

NOTICE FOR USER

- Please turn off power before install or change assembly parts.
- The input voltage and lamps should be matched, after connecting the power line, Please make sure the wiring section is insulated.
- No-professionals, must not install and disassemble the lamps.

TROUBLE SHOOTINGS

Troubles	Check points
Flickering of the light	Turn off the power and turn on again in 3 minutes. If same phenomena occur, then call agencies.
Out of working	Please check the connection.